



DN	L	D		B	C	H	n-Ød
		CL125/CL150	CL125/150				CL125/150
50	178	152	120.5	19	170	245	4-Ø18
65	190	178	139.5	19	170	268	4-Ø18
80	203	191	152.5	19	200	290	4-Ø18
100	229	229	190.5	24	220	315	8-Ø18
125	254	250	216	24	250	370	8-Ø22
150	267	279	241.5	26	250	410	8-Ø22
200	292	343	298.5	28	280	495	8-Ø22
250	330	406	362	30	450	628	12-Ø25
300	356	483	432	32	450	680	12-Ø25
400	406	597	539.5	40	550	730	12-Ø30

18	bolt	Carbon steel
17	bolt	SS304
16	bolt	SS304
15	gasket	SS304
14	Handwheel	GGG50
13	Gland	GGG50
12	Bonnet	GGG50
11	Dust ring	EPDM
10	copper bush	BRASS
9	o-ring	EPDM
8	Reverse sealing rubber ring	EPDM
7	Gasket	EPDM
6	Stem	BRONZE
5	Nut	BRONZE
4	Valve seat	BRONZE
3	Seal ring	BRONZE
2	Disc	GGG50
1	Body	GGG50
NO.	Name	Material

Application

- 1、Face to face is according to ANSI16.10
- 2、Flange drilled is according to B16.1/B16.5
- 3、working pressure:CL125-CL150.
- 4、Working temperature:-20° ~80℃,

Qingdao Judberd Machinery Co.,Ltd	
Metal Seated NRS AWWA C515 Gate Valve	