



| DN | L | D | | K | | G | | A | B | C | H | n-Ød | |
|-----|-----|------|------|------|------|------|------|---|----|-----|-----|--------|--------|
| | | PN10 | PN16 | PN10 | PN16 | PN10 | PN16 | | | | | PN10 | PN16 |
| 50 | 178 | 165 | 165 | 125 | 125 | 102 | 102 | 3 | 19 | 200 | 245 | 4-Ø19 | 4-Ø19 |
| 65 | 190 | 185 | 185 | 145 | 145 | 122 | 122 | 3 | 19 | 200 | 268 | 4-Ø19 | 4-Ø19 |
| 80 | 203 | 200 | 200 | 160 | 160 | 138 | 138 | 3 | 19 | 220 | 290 | 8-Ø19 | 8-Ø19 |
| 100 | 229 | 220 | 220 | 180 | 180 | 158 | 158 | 3 | 19 | 250 | 315 | 8-Ø19 | 8-Ø19 |
| 125 | 254 | 250 | 250 | 210 | 210 | 188 | 188 | 3 | 19 | 280 | 370 | 8-Ø19 | 8-Ø19 |
| 150 | 267 | 285 | 285 | 240 | 240 | 212 | 212 | 3 | 19 | 280 | 410 | 8-Ø23 | 8-Ø23 |
| 200 | 292 | 340 | 340 | 295 | 295 | 268 | 268 | 3 | 20 | 320 | 495 | 8-Ø23 | 12-Ø23 |
| 250 | 330 | 405 | 405 | 350 | 355 | 320 | 320 | 3 | 22 | 350 | 628 | 12-Ø23 | 12-Ø28 |
| 300 | 356 | 460 | 460 | 400 | 410 | 370 | 378 | 4 | 25 | 450 | 680 | 12-Ø23 | 12-Ø28 |

| DN | TR | Stem Diameter | 17 | 16 | 15 | 14 | 13 | 12 | 11 | 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
|-----|-------------|---------------|------|------|--------|-----------|-------|--------|-----------|-------------|--------|---------------|--------|------|-----|------------|-----------|------|------|
| 50 | TR18*4LH-BE | 18 | bolt | bolt | gasket | Handwheel | Gland | Bonnet | Dust ring | copper bush | o-ring | rubber gasket | Gasket | Stem | Nut | Valve seat | Seal ring | Disc | Body |
| 65 | TR18*4LH-BE | 18 | | | | | | | | | | | | | | | | | |
| 80 | TR20*4LH-BE | 20 | | | | | | | | | | | | | | | | | |
| 100 | TR24*4LH-BE | 24 | | | | | | | | | | | | | | | | | |
| 125 | TR28*6LH-BE | 28 | | | | | | | | | | | | | | | | | |
| 150 | TR28*6LH-BE | 28 | | | | | | | | | | | | | | | | | |
| 200 | TR32*6LH-BE | 32 | | | | | | | | | | | | | | | | | |
| 250 | TR38*6LH-BE | 36 | | | | | | | | | | | | | | | | | |
| 300 | TR38*6LH-BE | 38 | | | | | | | | | | | | | | | | | |

| NO. | Name | Material |
|-----|------|-----------------|
| | | Q235(galvanize) |
| | | SS304 |
| | | SS304 |
| | | GGG40 |
| | | GGG40 |
| | | NBR |
| | | Brass |
| | | NBR |
| | | EPDM |
| | | EPDM |
| | | 2CR13 |
| | | Brass (HPb59-1) |
| | | Brass (HPb59-1) |
| | | Brass (HPb59-1) |
| | | GGG40 |
| | | GGG40 |

Application

- 1、 Face to face is according to BS EN558-1,
- 2、 Flange drilled is according to BS EN1092-2,
- 3、 Working temperature: 0° ~ 80°C ,
- 4、 working pressure: PN10-PN16.

Qingdao judberd machinery co.,ltd

Metal Seated NRS BS5163 Gate Valve