



	L	D		K		G		A	B	C	H	n-ød	
		PN10	PN16	PN10	PN16	PN10	PN16					PN10	PN16
50	150	165	165	125	125	102	102	3	19	200	380	4-ø19	4-ø19
65	170	185	185	145	145	122	122	3	19	200	414	4-ø19	4-ø19
80	180	200	200	160	160	138	138	3	19	220	468	8-ø19	8-ø19
100	190	220	220	180	180	158	158	3	19	250	548	8-ø19	8-ø19
125	200	250	250	210	210	188	188	3	19	320	709	8-ø19	8-ø19
150	210	285	285	240	240	212	212	3	19	320	749	8-ø23	8-ø23
200	230	340	340	295	295	268	268	3	20	350	934	8-ø23	12-ø23
250	250	395	405	350	355	320	320	3	22	450	1138	12-ø23	12-ø27
300	270	445	460	400	410	370	378	4	25	450	1324	12-ø23	12-ø27

NO.	Name	Standard/Material	DN	TR	D8
22	Pin	SS304			
21	Gasket	Brass	50	TR18*4LH-8E	18
20	bolt	DIN912	65	TR18*4LH-8E	18
19	NUT	SS304	80	TR20*4LH-8E	20
18	Gasket	DIN125	100	TR24*4LH-8E	24
17	Double screw	DIN835	125	TR28*6LH-8E	28
16	Gasket	Brass	150	TR28*6LH-8E	28
15	Nut	Brass	200	TR32*6LH-8E	32
14	Handwheel	GGG50	250	TR36*6LH-8E	36
13	Nut	Brass	300	TR38*6LH-8E	38
12	yake	GGG50			
11	Gland	GGG50			
10	Packing	PTFE			
9	"O"ring	EPDM			
8	Packing	EPDM			
7	Bonnet	GGG50			
6	Stem	2CR13			
5	Nut	Brass (HPb59-1)			
4	Valve seat	Brass (HPb59-1)			
3	Seal ring	Brass (HPb59-1)			
2	Disc	GGG50			
1	Body	GGG50			



Application

- 1、Face to face is according to DIN EN558-1,
- 2、Flange drilled is according to DIN EN1092-2,
- 3、Working temperature:-20° ~80°C,
- 4、working pressure:PN10-PN16.

assembly drawing

Qingdao Judberd Machinery Co.,Ltd

os&y
Metal Seated
DIN3352-F4 Gate Valve