



**Application**

- 1、Face to face is according to BS EN558-1,
- 2、Flange drilled is according to BS EN1092-2,
- 3、Working temperature:0° ~ 80 °C ,
- 4、working pressure:PN10-PN16.

DN	L	D		K		G		A	B	C	H	n-φd	
		PN10	PN16	PN10	PN16	PN10	PN16					PN10	PN16
50	250	165	165	125	125	102	102	3	19	200	380	4-φ19	4-φ19
65	270	185	185	145	145	122	122	3	19	200	414	4-φ19	4-φ19
80	280	200	200	160	160	138	138	3	19	220	468	8-φ19	8-φ19
100	300	220	220	180	180	158	158	3	19	250	548	8-φ19	8-φ19
125	325	250	250	210	210	188	188	3	19	280	709	8-φ19	8-φ19
150	350	285	285	240	240	212	212	3	19	280	749	8-φ23	8-φ23
200	400	340	340	295	295	268	268	3	20	320	934	8-φ23	12-φ2
250	450	405	405	350	355	320	320	3	22	350	1138	12-φ23	12-φ2
300	500	460	460	400	410	370	378	4	25	450	1324	12-φ23	12-φ2

22	Pin	SS304	DN	TR	D8
21	Gasket	Brass	50	TR18*4LH-8E	18
20	bolt	DIN912	65	TR18*4LH-8E	18
19	NUT	SS304	80	TR20*4LH-8E	20
18	Gasket	DIN125	100	TR24*4LH-8E	24
17	Double screw	DIN835	125	TR28*6LH-8E	28
16	Gasket	Brass	150	TR28*6LH-8E	28
15	Nut	Brass	200	TR32*6LH-8E	32
14	Handwheel	GGG50	250	TR36*6LH-8E	36
13	Nut	Brass	300	TR38*6LH-8E	38
12	yake	GGG50			
11	Gland	GGG50			
10	Packing	PTFE			
9	"O"ring	EPDM			
8	Packing	EPDM			
7	Bonnet	GGG50			
6	Stem	2CR13			
5	Nut	Brass (HPb59-1)			
4	Valve seat	Brass (HPb59-1)			
3	Seal ring	Brass (HPb59-1)			
2	Disc	GGG50			
1	Body	GGG50			
NO.	Name	Standard/Material			

assembly drawing

Qingdao judberd Machinery co.,Ltd

os&y  
Metal seated gate valve

DIN3352-F5