



6	Gasket	1	EPDM
5	Pin	1	SS316L
4	Gasket	X	SS316L
3	Bolt	1	SS316L
2	Disc	1	CARBON+EPDM
1	Body	1	GGG50

DN	L	D		D1		D2		B	n-Ød	
		PN10	PN16	PN10	PN16	PN10	PN16		PN10	PN16
50	203	165	165	125	125	102	102	19	4-Ø19	4-Ø19
65	216	185	185	145	145	122	122	19	4-Ø19	4-Ø19
80	241	200	200	160	160	138	138	19	8-Ø19	8-Ø19
100	292	220	220	180	180	158	158	19	8-Ø19	8-Ø19
125	330	250	250	210	210	188	188	19	8-Ø19	8-Ø19
150	356	285	285	240	240	212	212	19	8-Ø23	8-Ø23
200	495	340	340	295	295	268	268	20	8-Ø23	12-Ø23
250	622	405	405	350	355	320	320	22	12-Ø23	12-Ø27
300	698	460	460	400	410	370	378	25	12-Ø23	12-Ø27
350	787	520	520	460	470	430	433	26.5	16-Ø23	16-Ø28
400	914	580	580	515	525	480	483	28	16-Ø28	16-Ø31
450	965	640	640	565	585	540	560	30	20-Ø28	20-Ø31
500	1067	715	715	620	650	585	610	32	20-Ø28	20-Ø34
600	1219	840	840	725	770	690	727	35	20-Ø31	20-Ø37

### Application

- 1、Face to face is according to EN558-1
- 2、Flange drilled is according to EN1092-2
- 3、Working temperature:  $-20^{\circ} \sim 80^{\circ}\text{C}$ ,
- 4、working pressure: PN10-PN16.